APPLICATION INSTRUCTIONS www.cheekyraskal.co.nz



Please read entire instruction sheet prior to applying your decal.

What you will need:










Most Cheeky Raskal decal's come in three layers. A white (sometimes blue) paper backing; the decal itself; and on most decals, the semi opaque sticky transfer paper on the top of the decal, which aides with


application.



Align your decal on the wall surface. To be completely it is straight and at the right height we recommend the use of a level and tape measure. Tape the corners of the decal to the wall with painter's tape.




Working from the middle of the image then outward to the edges, use your hand to smooth the side of the transfer tape so it adheres to the wall. Be sure to avoid bubbles and wrinkles.




Use the credit card to firmly rub across the entire vinyl graphic.




Clean the wall with a dry cloth. It is important to make sure the surface is free of dirt, dust and moisture. Important: If the wall has been freshly painted, please allow up to 6 weeks for the paint to cure.



Tape the decal to the wall with a strip of painter's tape across the middle, then remove the tape pieces from the corners of one side.




Use the credit card to firmly rub across the side of the vinyl graphic. This will remove any air bubbles and help the adhesion of the vinyl decal with the wall surface.



Starting with a corner and working diagonally, carefully pull the transfer tape from the surface of the wall and vinyl decal, ensuring that all the parts of the decals adhere to the wall.



Lay the decal on a flat surface such as a table. Use a credit card to rub firmly across the graphic to remove any bubbles and to strengthen the bond between the transfer tape and the graphic.



Peel back one side of the transfer tape from the white backing sheet, ensuring that the decal sticks to the transfer tape. Using scissors, cut away the side of the white backing paper that is revealed.



Remove the strip of painter;s tape. Pull the remaining which backing paper from the back of the decal and smooth the decal down with your hands as you go. Avoid bubbles and wrinkles.



Use a clean cloth and rub over the decal to remove and air bubbles that might remain. You can use a small pin to poke the bubbles as well.